Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ETTROIT

Supplier's address: Regulatory Affairs, CORSO VITTORIO EMANUELE 110, 80121 Napoli Napoli Napoli, IT

Model identifier: ET4104

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	No cap / Integrated LED light source		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	5	Energy efficiency class	G
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	236 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	5,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	61
Outer dimensions without separate con-	Height: 17	Spectral power distribution in the	See image in last page
	Width: 10		
	Depth: 12		

trol gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power[a]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,460 0,420
Parameters for LED and OLED light sources:				
R9 colour rendering index value		-65	Survival factor	-
the lumen maintenance factor		0,90		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,71	Colour consistency in McAdam ellipses	9
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[b]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	-

[a] '-' : not applicable;

[b] '-' : not applicable;

Spectrum


Spectrum
1.0 = 5.105e+000mW/nm
1.2
1.0
0.8
0.6
0.4
0.2
0.0
380
480
580
680
780
Wavelength(nm)
13.2 SDCM
x=0.463 y=0.420 F2700

EPREL registration number: 2752233 Model placed on the Union market from 01/06/2026.	https://eprel.ec.europa.eu/qr/2752233

Complementary information (not part of the compliance assessment):

Commercial name or trade designation: CATENA 100LED 10M FILO NERO LUCE GIALLO IP65

GTIN identifier: 8059692404315

Supplier: SPACE - C S.R.L. (Manufacturer) **Website:** www.ettroit.com

Customer care service:

Name: Regulatory Affairs **Website:** www.ettroit.com

Email: info@space-c.net **Phone:** +393935068456

Address:
CORSO VITTORIO EMANUELE 110
80121 Napoli
Italy