# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ETTROIT

**Supplier's address:** Regulatory Affairs, CORSO VITTORIO EMANUELE 110, 80121 Napoli Napoli Napoli, IT

**Model identifier:** ET4129

**Type of light source:**

| | | | |
|---|---|---|---|
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | No cap / Integrated LED light source | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |

**Product parameters**

| Parameter | Value | Parameter | Value |
|---|---|---|---|
| **General product parameters:** | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 9 | Energy efficiency class | G |
| Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º) | 453 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 500 |
| On-mode power ($P_{on}$), expressed in W | 8,8 | Standby power ($P_{sb}$), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power ($P_{net}$) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 79 |
| Outer dimensions without separate con- | Height | 24 | Spectral power distribution in the | See image in last page |
| | Width | 12 | | |
| | Depth | 17 | | |

| | | | | |
|---|---|---|---|---|
| trol gear, lighting control parts and non-lighting control parts, if any (millimetre) | | | range 250 nm to 800 nm, at full-load | |
| Claim of equivalent power[a] | | - | If yes, equivalent power (W) | - |
| | | | Chromaticity coordinates (x and y) | 0,313<br>0,337 |
| **Parameters for LED and OLED light sources:** | | | | |
| R9 colour rendering index value | | 5 | Survival factor | 0,90 |
| the lumen maintenance factor | | 0,90 | | |
| **Parameters for LED and OLED mains light sources:** | | | | |
| displacement factor (cos ϕ1) | | 0,75 | Colour consistency in McAdam ellipses | 9 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | | -[b] | If yes then replacement claim (W) | - |
| Flicker metric (Pst LM) | | 1,0 | Stroboscopic effect metric (SVM) | - |

[a] '-' : not applicable;

[b] '-' : not applicable;

## Test Condition

| | | | |
|---|---|---|---|
| Temprature | : 25.0Deg | RH | : 63% |
| WL Range | : 380nm-780nm | IP | : 46729 (71%) |
| Test Mode | : Fast Test | T | : 255 ms |
| Sensitivity | : High | | |

## Spectrum




## Colorimetric Parameters

Chromaticity Coordinate: x = 0.2445 y = 0.2377 / u' = 0.1823 v' = 0.3988 (duv=-1.66e-03)

CCT= 87520K Prcp WL: Ld=475.5nm Purity=39.4%

Peak WL: Lp=450nm FWHM: =22.0nm Ratio:R=9.2% G=81.8% B=8.9%

| | |
|---|---|
| **EPREL registration number:** 2752863<br><br>Model placed on the Union market from 01/06/2026. | https://eprel.ec.europa.eu/qr/2752863 |

**Complementary information (not part of the compliance assessment):**

**Commercial name or trade designation:** TENDA 200LED 5M X 50CM FILO BIANCO LUCE BIANCO IP65

**GTIN identifier:** 8059692404568

**Supplier:** SPACE - C S.R.L. (Manufacturer) **Website:** www.ettroit.com

**Customer care service:**

**Name:** Regulatory Affairs **Website:** www.ettroit.com

**Email:** info@space-c.net **Phone:** +393935068456

**Address:**
CORSO VITTORIO EMANUELE 110
80121 Napoli
Italy