Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ETTROIT

Supplier's address: Regulatory Affairs, CORSO VITTORIO EMANUELE 110, 80121 Napoli Napoli Napoli, IT

Model identifier: ET4106

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	No cap / Integrated LED light source		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	G
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	49 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	99 999
On-mode power (P_{on}), expressed in W	6,2	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	1
Outer dimensions without separate con-	Height	17	Spectral power distribution in the	See image in last page
	Width	10		
	Depth	-		

trol gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power[a]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,360 0,366
Parameters for directional light sources:				
Peak luminous intensity (cd)		15	Beam angle in degrees, or the range of beam angles that can be set	180
Parameters for LED and OLED light sources:				
R9 colour rendering index value		-224	Survival factor	0,90
the lumen maintenance factor		0,90		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,74	Colour consistency in McAdam ellipses	9
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[b]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	-

[a] '-' : not applicable;

[b] '-' : not applicable;

Spectrum



Colorimetric Parameters

Chromaticity Coordinate: x = 0.1497 y = 0.0397 / u' = 0.1885 v' = 0.1124 (duv=-1.91e-01)
CCT>=100000K Prcp WL: Ld=460.2nm Purity=96.8%
Peak WL: Lp=454nm FWHM: =21.2nm Ratio:R=1.6% G=20.3% B=78.1%

Render Index: Ra = -46.0
R1 =8 R2 =-31 R3 =-147 R4 =-90 R5 =19 R6 =-38 R7 =-49
R8 =-40 R9 =-224 R10=-203 R11=-116 R12=-94 R13=-6 R14=-31 R15=20
WHITE:OUT

EPREL registration number: 2752694 Model placed on the Union market from 01/06/2026.	https://eprel.ec.europa.eu/qr/2752694

Complementary information (not part of the compliance assessment):

Commercial name or trade designation: CATENA 100LED 10M FILO NERO LUCE BLU IP65

GTIN identifier: 8059692404339

Supplier: SPACE - C S.R.L. (Manufacturer) **Website:** www.ettroit.com

Customer care service:

Name: Regulatory Affairs **Website:** www.ettroit.com

Email: info@space-c.net **Phone:** +393935068456

Address:
CORSO VITTORIO EMANUELE 110
80121 Napoli
Italy