Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ETTROIT

Supplier's address: Regulatory Affairs, CORSO VITTORIO EMANUELE 110, 80121 Napoli Napoli Napoli, IT

Model identifier: ET4125

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	No cap / Integrated LED light source		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	G
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	67 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	99 999
On-mode power (P_{on}), expressed in W	5,4	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	1
Outer dimensions without separate con-	Height	19	Spectral power distribution in the	See image in last page
	Width	11		
	Depth	14		

trol gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power[a]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,360 0,366
Parameters for LED and OLED light sources:				
R9 colour rendering index value		-23	Survival factor	0,90
the lumen maintenance factor		0,90		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,94	Colour consistency in McAdam ellipses	9
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[b]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	-

[a] '-' : not applicable;

[b] '-' : not applicable;

Test Condition

Temprature	: 25.0Deg	RH	: 63%
WL Range	: 380nm-780nm	IP	: 50229 (77%)
Test Mode	: Fast Test	T	: 233 ms
Sensitivity	: High		

Spectrum



EPREL registration number: 2752843 Model placed on the Union market from 01/06/2026.	https://eprel.ec.europa.eu/qr/2752843

Complementary information (not part of the compliance assessment):

Commercial name or trade designation: TENDA 120LED 3M X30-70-40-60 FILO BIANCO LUCE BLU IP65

GTIN identifier: 8059692404520

Supplier: SPACE - C S.R.L. (Manufacturer) **Website:** www.ettroit.com

Customer care service:

Name: Regulatory Affairs **Website:** www.ettroit.com

Email: info@space-c.net **Phone:** +393935068456

Address:
CORSO VITTORIO EMANUELE 110
80121 Napoli
Italy